

BRONZE SELF PRIMING ELECTRIC PUMPS



Self priming electric pumps in bronze, monobloc execution with open impeller that allows the passage of big solids. Pumps suitable for sea water and circulation of the same in swimming pools. Pump casing, flange, impeller and valve are in bronze. Shaft is in stainless steel

Cat. Cat. Cat.	Pompa Pump	HP HP CV	KW KW	Motore Motor Moteur	Aspirazione Mandata Suction Delivery	Peso Weight Poids (Kg)	Dimensioni Dimensions LxLxH (mm)	H Q	Prestazioni Performances Performances	Prezzo Price-Prix		
EA9M	B1KQ-A/B	0,5	0,37	230 M.	1"	19	215	mt	3	6	9	12
EA9N				230/400 T.	1"		275	l/m'	110	90	65	35
EA7C	B4YKQ-A/B	1	0,75	230 M.	1 1/2"	21	220	mt	6	9	12	16
EA8D				230/400 T.	1 1/2"		375	l/m'	300	260	190	70
EAS8	B2KQ-A/B	2	1,5	230 M.	2"	27,5	185	mt	5	10	15	18
EAS9				230/400 T.	2"		410	l/m'	480	400	230	100
EAT1	B3KQ-A/B	3	2,2	230 M.	3"	33	185	mt	4	8	12	16
EAT2				230/400 T.	3"		445	l/m'	900	740	500	200
EAB4	B4KQ-A/B	5,5	4	400/690 T.	4"	70	315	mt	4	8	10	12
EA9H				230 M.	4"		670	l/m'	1650	1350	1050	750
EA4R	G2TMK-A/B	3	2,2	230 M.	2"	37	230	mt	15	20	25	33
EAD6				230/400 T.	2"		450	l/m'	310	270	220	110
EAD7	G3TMK-A/B	5,5	4	400/690 T.	3"	70	280	mt	10	15	25	30
EAD8				230 M.	3"		650	l/m'	750	650	450	100
EAD9	G3TMK-A/B	7,5	5,5	400/690 T.	3"	77	410	mt	10	20	25	33
EABH				230 M.	3"		670	l/m'	950	720	570	280
EAB5	B3XR-A/B	5,5	4	400/690 T.	3"	80	280	mt	15	25	35	38
EAC4				230 M.	3"		410	l/m'	1150	900	600	400
EAB6	B3XR-A/B	10	7,5	400/690 T.	3"	99	280	mt	15	25	35	44
EAC3				230 M.	3"		720	l/m'	1240	1080	800	400
EAB7	B4XR-A/B	15	11	400/690 T.	3"	103	280	mt	20	30	40	47
EAFD				230 M.	3"		720	l/m'	1300	1100	800	500
EADV	B3ZPM-A/B	5,5	4	400/690 T.	3"	65	280	mt	5	15	20	25
EAC4				230 M.	3"		635	l/m'	1100	800	630	370
EAB6	B3XR-A/B	7,5	5,5	400/690 T.	3"	70,5	280	mt	5	15	20	25
EAC3				230 M.	3"		650	l/m'	1350	920	780	600
EAB7	B4XR-A/B	10	7,5	400/690 T.	3"	76,5	405	l/m'	10	15	20	25
EAFD				230 M.	3"		280	mt	1650	1450	1250	920
EADV	B3ZPM-A/B	15	11	400/690 T.	4"	117	365	mt	10	15	20	28
EAB7				230 M.	4"		800	l/m'	2350	2200	1900	600
EAFD	B3ZPM-A/B	20	15	400/690 T.	4"	122	365	mt	15	20	25	28
EADV				230 M.	4"		800	l/m'	2550	2350	1900	1200
EAFD	B3ZPM-A/B	20	15	400/690 T.	3"	121	330	mt	32	45	50	55
EADV				230 M.	3"		750	l/m'	1330	1000	800	480
EADV	B3ZPM-A/B	25	18,5	400/690 T.	3"	186	420	mt	50	60	65	70
EADV				230 M.	3"		910	l/m'	1200	970	800	550

