



## AISI 316 STAINLESS STEEL SELF PRIMING ELECTRIC PUMPS

Self priming pumps in stainless steel, suitable for acid waters, sewage, for transferring dilute acid, pumping fluid food stuff and recovery of losses from chemical equipments. Impeller, valve and pump casing are in AISI 316 stainless steel. On request we can supply these pumps with special mechanical seals (Viton)



| Cat. Cat. | Pompa Pump   | HP HP | KW KW | Motore Motor | Aspirazione Mandata Suction Delivery | Dimensioni Dimensions LxLxH (mm) | H Q  | Prestazioni Performances | Prezzo Price-Price |      |      |      |
|-----------|--------------|-------|-------|--------------|--------------------------------------|----------------------------------|------|--------------------------|--------------------|------|------|------|
|           |              | CV    | KW    | Moteur       |                                      |                                  |      | Performances             |                    |      |      |      |
|           |              |       |       |              |                                      |                                  |      | Performances             |                    |      |      |      |
| EA7G      | B2KQ-A/INOX  | 2     | 1,5   | 230 M.       | 2"                                   | 185<br>410                       | mt   | 5                        | 10                 | 12   | 17   |      |
| EA7E      |              |       |       | 230/400 T.   | 2"                                   |                                  |      | l/m'                     | 450                | 345  | 300  | 100  |
|           |              |       |       |              | 3"                                   |                                  |      | mt                       | 10                 | 15   | 25   | 30   |
| EACA      | G3TMK-A/INOX | 5,5   | 4     | 400/690 T.   | 3"                                   | 66                               | l/m' | 750                      | 650                | 450  | 100  |      |
| EACB      |              |       |       |              | 3"                                   |                                  |      | mt                       | 10                 | 20   | 25   | 33   |
| EACB      | G3TMK-A/INOX | 7,5   | 5,5   | 400/690 T.   | 3"                                   | 73                               | l/m' | 950                      | 720                | 570  | 280  |      |
| EABE      |              |       |       |              | 3"                                   |                                  |      | mt                       | 15                 | 25   | 35   | 38   |
| EACC      | G3TMK-A/INOX | 10    | 7,5   | 400/690 T.   | 3"                                   | 76                               | l/m' | 1150                     | 900                | 600  | 400  |      |
| EACD      |              |       |       |              | 3"                                   |                                  |      | mt                       | 15                 | 25   | 35   | 44   |
| EACC      | G3TMK-A/INOX | 12,5  | 9,2   | 400/690 T.   | 3"                                   | 95                               | l/m' | 1240                     | 1080               | 800  | 400  |      |
| EACD      |              |       |       |              | 3"                                   |                                  |      | mt                       | 20                 | 30   | 40   | 47   |
| EACD      | G3TMK-A/INOX | 15    | 11    | 400/690 T.   | 3"                                   | 99                               | l/m' | 1300                     | 1100               | 800  | 500  |      |
| EAD2      | B3XR-A/INOX  | 5,5   | 4     | 400/690 T.   | 3"                                   | 59,5                             | mt   | 5                        | 15                 | 20   | 25   |      |
|           |              |       |       |              | 3"                                   |                                  |      | l/m'                     | 1100               | 800  | 630  | 370  |
| EAC6      | B3XR-A/INOX  | 7,5   | 5,5   | 400/690 T.   | 3"                                   | 66                               | mt   | 5                        | 15                 | 20   | 25   |      |
|           |              |       |       |              | 3"                                   |                                  |      | l/m'                     | 1320               | 920  | 780  | 600  |
| EAC7      | B3XR-A/INOX  | 10    | 7,5   | 400/690 T.   | 3"                                   | 72                               | mt   | 10                       | 15                 | 20   | 25   |      |
|           |              |       |       |              | 3"                                   |                                  |      | l/m'                     | 1650               | 1450 | 1250 | 920  |
| EAF9      | B4XR-A/INOX  | 15    | 11    | 400/690 T.   | 4"                                   | 110                              | mt   | 10                       | 15                 | 20   | 28   |      |
|           |              |       |       |              | 4"                                   |                                  |      | l/m'                     | 2350               | 2200 | 1900 | 600  |
| EAAC      | B4XR-A/INOX  | 20    | 15    | 400/690 T.   | 4"                                   | 115                              | mt   | 15                       | 20                 | 25   | 28   |      |
|           |              |       |       |              | 4"                                   |                                  |      | l/m'                     | 2550               | 2350 | 1900 | 1200 |

